



**Easy to install.**  
**Connects to workshop vacs**  
**and**  
**Dust collectionsystems**






**WARNING! BLADE EXPOSURE. INSTALL, MAINTAIN AND REMOVE DUST CUTTER SYSTEM WITH SAW OFF AND UNPLUGGED.**

**SAFETY INSTRUCTIONS**


1. Before installing or removing the Dust Cutter, turn off and UNPLUG table saw
2. Do not cut, grind or sand metals or use any materials that produce sparks, with the Dust Cutter installed.
3. Always operate the table saw with the safety guard in place, properly adjusted and in good working order.
4. Do not clear or empty dust from the Dust Cutter while the saw is operating.
5. Do not install the Dust Cutter on any saw in any other manner than described in the installation section below.
6. Empty the Dust Cutter frequently to prevent excessive dust which could result in a fire hazard.
7. Openings in the table saw or between the table saw and the stand should not be blocked unless approved by the table saw manufacturer.
8. Frequently empty vacuum, clean filter and check vac connections.

**How To Install**


1. Unplug & turn saw over, resting work surface face down on floor.
2. Lightly sand inside top of stand struts.  
Clean sanded area with water or solvent (no soap or detergent)
3. Cut and apply hook fastener to stand struts above or between bolts. Wait 24 hours for adhesive on hook fastener to dry.
4. Install bag with vacuum connection at rear of machine.
5. Turn saw upright, it's now ready for use.




**Optional Steps - for bolting the bag to the stand for permanent attachment**



1. A Remove bolt(s) from top of stand legs.



2. A If bolting bag to stand, apply each side in line with and over bolt holes.



3. A Drill holes in hook & loop fastener thru bolt holes and re-install bolts.

**OPTIONAL STEPS**

# OPERATING MODES

## Collector Mode

- Leave zipper closed and vacuum connector plugged.
- To empty, place container under the bag, open the zipper and shake dust out of the bag.



## Funnel Mode

- Place empty container under the bag and open the zipper.



## Vacuum Mode

- Remove vacuum connector plug and insert hose - note that 1-1/4" hose fits into internal baffle connection
- Turn vacuum on and then turn on saw
- To remove obstructions, first unplug saw

